

TRACK CONDITIONS Indoor Tight Smooth Hard Packed Blue Groove
 Wet Low Bite High Bite Outdoor Open Rough Loose/Loamy
 Dry Dusty Wed Bite Other _____

ENGINE Gasket _____ mm Plug _____ Muffler _____ Fuel _____
 Clutch bell 16T 17T 18T Other _____ T Shoes 3 4 Spring _____ mm

DIFF Front _____ Oil # _____ Center _____ Oil # _____ Rear _____ Oil # _____
 T x T Spur gear T T x T

FRONT SUSPENSION

Tire # _____ Camber Deg. _____
 Off Set + mm _____
 Inner # _____

FRONT TOE ANGLE | CASTER ANGLE

22° 24° 26°
 Other _____ Deg.

FRONT SHOCK

Oil # _____

PISTON
 #0096-0815 6x1.5mm
 #0096-0812 8x1.2mm
 #0096-0813 8x1.3mm
 others

CONE OF PISTON
 DOWN UP

SHOCK SPRINGS
 #9680 Black-Red dot
 #9685 Black-Orange dot
 #9690 Black-Yellow dot
 others

Spacer mm _____
 Length mm _____

KICK UP

FF FR

ANTI ROLL BAR FRONT

#8019 U Type 1.9mm
 #8021 U Type 2.1mm
 #8022 U Type 2.2mm
 #8023 U Type 2.3mm
 #8024 U Type 2.4mm
 #8025 U Type 2.5mm
 others

U Type

ANTI SQUAT | TOE ANGLE

RF RR

WHEEL BASE

Washer mm _____ pcs _____

 Washer mm _____ pcs _____

REAR SHOCK

Oil # _____

PISTON
 #0096-0815 6x1.5mm
 #0096-0812 8x1.2mm
 #0096-0813 8x1.3mm
 others

CONE OF PISTON
 DOWN UP

SHOCK SPRINGS
 #9785 Black-Red dot
 #9790 Black-Orange dot
 #9795 Black-Yellow dot
 others

Spacer mm _____
 Length mm _____

REAR SUSPENSION

Tire # _____ Camber Deg. _____
 Off Set + mm _____
 Inner # _____

WING POSITION

ANTI ROLL BAR REAR

#8322 U Type 2.2mm
 #8323 U Type 2.3mm
 #8324 U Type 2.4mm
 #8325 U Type 2.5mm
 #8326 W Type 2.6mm
 #8328 W Type 2.8mm
 #8330 W Type 3.0mm
 others

U Type W Type(OP)

DROOP LIMITER

To Adjust with Down Stop Screw

Droop _____

Front mm _____ Rear mm _____

ACKERMAN

RIDE HEIGHT

Front mm _____ Rear mm _____